

**P10467 - FIBERFIP ADESIVO 800 COMP.A****Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

**SECTION 1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Code: **P10467**  
 Product name: **FIBERFIP ADESIVO 800 COMP.A**  
 UFI: **NK80-J0JQ-3000-TC0P**

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Intended use: **Adesivo epossidico**

**1.3. Details of the supplier of the safety data sheet**

Name: **Licata S.p.A.**  
 Full address: **Via De Gasperi,155**  
 District and Country: **92024 Canicatti (AG) Italia**  
 Tel.: **+39 0922 856088**  
 Fax: **+39 0922 831427**  
 e-mail address of the competent person responsible for the Safety Data Sheet: **controllo-qualita@licataspa.it**

**1.4. Emergency telephone number**

For urgent inquiries refer to:  
**NHS111in England: 111**  
**NHS24in Scotland: 111**  
**NHS Direct in Wales: 111 or 0845 4647**  
**In an emergency, if the patient has collapsed or is not breathing properly, call 999**

**SECTION 2. Hazards identification****2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

## Hazard classification and indication:

Carcinogenicity, category 1B	H350	May cause cancer.
Germ cell mutagenicity, category 1B	H340	May cause genetic defects.
Reproductive toxicity, category 1B	H360F	May damage fertility.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity, category 2	H411	Toxic to aquatic life with long lasting effects.

**2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

**P10467 - FIBERFIP ADESIVO 800 COMP.A****SECTION 2. Hazards identification ... / >>**

## Hazard statements:

<b>H350</b>	May cause cancer.
<b>H340</b>	May cause genetic defects.
<b>H360F</b>	May damage fertility.
<b>H315</b>	Causes skin irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H411</b>	Toxic to aquatic life with long lasting effects. Restricted to professional users.

## Precautionary statements:

<b>P201</b>	Obtain special instructions before use.
<b>P280</b>	Wear protective gloves/ protective clothing / eye protection / face protection.
<b>P308+P313</b>	IF exposed or concerned: Get medical advice / attention.
<b>P273</b>	Avoid release to the environment.
<b>P391</b>	Collect spillage.
<b>P261</b>	Avoid breathing dust / fume / gas / mist / vapours / spray.

**Contains:**

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM  
OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS  
REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)

Product not intended for uses provided for by Directive 2004/42/EC.

**2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

## Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)</b>		
INDEX	$86 \leq x < 90$	<b>Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411</b>
EC	701-263-0	<b>Skin Irrit. 2 H315: <math>\geq</math> 5%</b>
CAS	9003-36-5	
REACH Reg.	01-2119454392-40-0010	
<b>OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS</b>		
INDEX	$6 \leq x < 7$	<b>Repr. 1B H360F, Eye Irrit. 2 H319, Skin Sens. 1 H317</b>
EC	271-846-8	
CAS	68609-97-2	
REACH Reg.	01-2119485289-22-XXXX	
<b>SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM</b>		
INDEX	$0,25 \leq x < 0,3$	<b>Carc. 1B H350, Muta. 1B H340, Asp. Tox. 1 H304, Classification note according to Annex VI to the CLP Regulation: P</b>
EC	265-199-0	
CAS	64742-95-6	
<b>2-METHOXY-1-METHYLETHYL ACETATE</b>		
INDEX	$0,2 \leq x < 0,25$	<b>Flam. Liq. 3 H226</b>
EC	203-603-9	
CAS	108-65-6	
<b>N-BUTYL ACETATE</b>		
INDEX	$0,15 \leq x < 0,2$	<b>Flam. Liq. 3 H226, STOT SE 3 H336, EUH066</b>
EC	204-658-1	
CAS	123-86-4	

**P10467 - FIBERFIP ADESIVO 800 COMP.A****SECTION 3. Composition/information on ingredients** ... / >>**XYLENE**

INDEX 601-022-00-9 0,1 ≤ x &lt; 0,15

**Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C**EC 215-535-7  
CAS 1330-20-7  
REACH Reg. 01-2119488216-32**ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l**

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures****4.1. Description of first aid measures**

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

**4.3. Indication of any immediate medical attention and special treatment needed**

IF exposed or concerned: Get medical advice / attention.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

**SECTION 5. Firefighting measures****5.1. Extinguishing media**

## SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

## UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

**5.2. Special hazards arising from the substance or mixture**

## HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

**5.3. Advice for firefighters**

## GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of

**P10467 - FIBERFIP ADESIVO 800 COMP.A**

contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**6.2. Environmental precautions**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

**7.2. Conditions for safe storage, including any incompatibilities**

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

**2-METHOXY-1-METHYLETHYL ACETATE**

Store in an inert atmosphere, sheltered from moisture because it hydrolyses easily.

**7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Regulatory references:

DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU)

**P10467 - FIBERFIP ADESIVO 800 COMP.A****SECTION 8. Exposure controls/personal protection ... / >>**

2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.  
ACGIH 2023

TLV-ACGIH

**OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS****Predicted no-effect concentration - PNEC**

Normal value in fresh water	1,12	mg/l
Normal value in marine water	0,112	mg/l
Normal value for fresh water sediment	1,05	mg/kg
Normal value for marine water sediment	0,105	mg/kg
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	20	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,05 mg/kg bw/d				
Inhalation				0,087 mg/m3				0,49 mg/m3
Skin				0,089 mg/kg bw/d				0,75 mg/kg bw/d

**REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)****Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,003	mg/l
Normal value in marine water	0,0003	mg/l
Normal value for fresh water sediment	0,294	mg/kg/d
Normal value for marine water sediment	0,0294	mg/kg/d
Normal value for fresh water, intermittent release	0,0254	mg/l
Normal value of STP microorganisms	10	mg/l

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				6,25 mg/kg bw/d				
Inhalation				8,7 mg/m3		29,39 mg/m3		
Skin				62,5 mg/kg bw/d	8,3 mg/kg bw/d			104,15 mg/kg bw/d

**P10467 - FIBERFIP ADESIVO 800 COMP.A****SECTION 8. Exposure controls/personal protection ... / >>****XYLENE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	220	50	440	100	SKIN
MAK	DEU	220	50	440	100	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
GVI/KGVI	HRV	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
MV	SVN	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH			20			

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg
Normal value of STP microorganisms	6,58	mg/l
Normal value for the terrestrial compartment	2,31	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation					442	442	221	221
					mg/m3	mg/m3	mg/m3	mg/m3
Skin								212
								mg/kg
								bw/d

**2-METHOXY-1-METHYLETHYL ACETATE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
VLA	ESP	275	50	550	100	SKIN
VLEP	FRA	275	50	550	100	SKIN
GVI/KGVI	HRV	275	50	550	100	SKIN
VLEP	ITA	275	50	550	100	SKIN
MV	SVN	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

**N-BUTYL ACETATE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	300	62	600	124	
MAK	DEU	480	100	960	200	
VLA	ESP	241	50	723	150	
VLEP	FRA	241	50	723	150	
GVI/KGVI	HRV	241	50	723	150	
VLEP	ITA	241	50	723	150	
MV	SVN	300	62	600	124	
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	

**Legend:**

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

**8.2. Exposure controls**

**P10467 - FIBERFIP ADESIVO 800 COMP.A****SECTION 8. Exposure controls/personal protection ... / >>**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

The product must be used inside a closed circuit, in a well-ventilated environment and with strong localised aspiration systems in place.

**HAND PROTECTION**

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN ISO 16321).

**RESPIRATORY PROTECTION**

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	not available	
Colour	not available	
Odour	not available	
Melting point / freezing point	not available	
Initial boiling point	> 200 °C	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	> 200 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	
Kinematic viscosity	not available	
Dynamic viscosity	30000 cPs a 23°C	
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	not available	
Relative vapour density	not available	
Particle characteristics	not applicable	

**9.2. Other information****9.2.1. Information with regard to physical hazard classes**

Information not available

**9.2.2. Other safety characteristics**

**P10467 - FIBERFIP ADESIVO 800 COMP.A****SECTION 9. Physical and chemical properties** ... / >>

VOC (Directive 2010/75/EU)	3,15 %
VOC (volatile carbon)	1,70 %

**SECTION 10. Stability and reactivity****10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)

Stable in normal conditions of use and storage.

2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

1,2-PROPANEDIOL

Hygroscopic. Stable in normal conditions of use and storage.

At high temperatures it tends to oxidate to form propionaldehyde and lactic and acetic acid.

N-BUTYL ACETATE

Decomposes on contact with: water.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)

Stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

No hazardous reactions are foreseeable in normal conditions of use and storage.

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)

Stable in normal conditions of use and storage.

XYLENE

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances, strong acids, alkaline metals.

1,2-PROPANEDIOL

May react dangerously with: acid chlorides, acid anhydrides, oxidising agents.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react dangerously with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

**10.4. Conditions to avoid**

None in particular. However the usual precautions used for chemical products should be respected.

N-BUTYL ACETATE

Avoid exposure to: moisture, sources of heat, naked flames.

**10.5. Incompatible materials**

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)

Incompatible with: strong acids, strong alkalis, amines, strong oxidising agents.

2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances, strong acids, alkaline metals.

N-BUTYL ACETATE

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

**10.6. Hazardous decomposition products**

1,2-PROPANEDIOL

May develop: carbon oxides.

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**P10467 - FIBERFIP ADESIVO 800 COMP.A****SECTION 11. Toxicological information ... / >>****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**Metabolism, toxicokinetics, mechanism of action and other information**2-METHOXY-1-METHYLETHYL ACETATE**

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure**XYLENE**

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

**2-METHOXY-1-METHYLETHYL ACETATE**

WORKERS: inhalation; contact with the skin.

**N-BUTYL ACETATE**

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**XYLENE**

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

**2-METHOXY-1-METHYLETHYL ACETATE**

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

**N-BUTYL ACETATE**

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

Interactive effects**XYLENE**

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

**N-BUTYL ACETATE**

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

**OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS**

LD50 (Dermal):	> 4000 mg/kg Coniglio
LD50 (Oral):	> 2000 mg/kg Ratto
LC50 (Inhalation vapours):	> 0,15 mg/l Ratto

**REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)**

LD50 (Dermal):	> 2000 mg/kg Coniglio
LD50 (Oral):	> 2000 mg/kg Ratto

**P10467 - FIBERFIP ADESIVO 800 COMP.A****SECTION 11. Toxicological information ... / >>**

<b>XYLENE</b>	
LD50 (Dermal):	4350 mg/kg Rabbit
ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	26 mg/l/4h Rat
<b>AMORPHOUS SILICATE HYDRATE</b>	
LD50 (Dermal):	> 2000 mg/kg Rat
LD50 (Oral):	> 2000 mg/kg Rat
LC50 (Inhalation mists/powders):	> 2,2 mg/l/1h Rat
<b>2-METHOXY-1-METHYLETHYL ACETATE</b>	
LD50 (Dermal):	> 5000 mg/kg Rat
LD50 (Oral):	8530 mg/kg Rat
<b>1,2-PROPANEDIOL</b>	
LD50 (Dermal):	20800 mg/kg Rat
LD50 (Oral):	20800 mg/kg Rat
<b>N-BUTYL ACETATE</b>	
LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 6400 mg/kg Rat
LC50 (Inhalation vapours):	21,1 mg/l/4h Rat
<b>SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM</b>	
LD50 (Dermal):	> 2000 mg/kg RATTO
LD50 (Oral):	> 2000 mg/kg RATTO

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

May cause genetic defects

CARCINOGENICITY

May cause cancer

**XYLENE**

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).  
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

May damage fertility

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**P10467 - FIBERFIP ADESIVO 800 COMP.A****SECTION 11. Toxicological information ... / >>****11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

**SECTION 12. Ecological information**

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it has negative effects on the aquatic environment.

**12.1. Toxicity**

## OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS

LC50 - for Fish	> 5000 mg/l/96h
Chronic NOEC for Crustacea	56 mg/l Daphnia magna

## REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)

LC50 - for Fish	2,54 mg/l/96h
EC50 - for Crustacea	2,55 mg/l/48h
EC50 - for Algae / Aquatic Plants	1,8 mg/l/72h
EC10 for Crustacea	0,3 mg/l/28d

## 2-METHOXY-1-METHYLETHYL ACETATE

LC50 - for Fish	> 100 mg/l/96h
EC50 - for Crustacea	373 mg/l/48h

## SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM

LC50 - for Fish	5 mg/l/96h
EC50 - for Crustacea	5 mg/l/48h
EC50 - for Algae / Aquatic Plants	5 mg/l/72h

**12.2. Persistence and degradability**

## REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)

NOT rapidly degradable

## XYLENE

Solubility in water	100-1000 mg/l
Rapidly degradable	

## AMORPHOUS SILICATE HYDRATE

Solubility in water	0,1 - 100 mg/l
Degradability: information not available	

## 1,2-PROPANEDIOL

Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

## N-BUTYL ACETATE

Solubility in water	1000 - 10000 mg/l
---------------------	-------------------

## SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM

Rapidly degradable

**12.3. Bioaccumulative potential**

## XYLENE

Partition coefficient: n-octanol/water	3,12
BCF	25,9

## AMORPHOUS SILICATE HYDRATE

Partition coefficient: n-octanol/water	0,53
--	------

## 1,2-PROPANEDIOL

Partition coefficient: n-octanol/water	-1,07
BCF	0,09

**P10467 - FIBERFIP ADESIVO 800 COMP.A****SECTION 12. Ecological information** ... / >>

N-BUTYL ACETATE  
Partition coefficient: n-octanol/water 2,3  
BCF 15,3

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

**12.7. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information****14.1. UN number or ID number**

ADR / RID, IMDG, IATA: UN 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity  $\leq$  5Kg or 5L, is not submitted to ADR provisions.

IMDG: In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity  $\leq$  5Kg or 5L, is not submitted to IMDG Code provisions.

IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity  $\leq$  5Kg or 5L, is not submitted to IATA dangerous goods regulations.

**14.2. UN proper shipping name**

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin (number average molecular weight  $\leq$ 700); Reaction product: bisphenol-F-epichlorohydrin; epoxy resin (number average molecular weight  $\leq$  700))

IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin (number average molecular weight  $\leq$ 700); Reaction product: bisphenol-F-epichlorohydrin; epoxy resin (number average molecular weight  $\leq$  700))

IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin (number average molecular weight  $\leq$ 700); Reaction product: bisphenol-F-epichlorohydrin; epoxy resin (number average molecular weight  $\leq$  700))

**P10467 - FIBERFIP ADESIVO 800 COMP.A****SECTION 14. Transport information** ... / >>**14.3. Transport hazard class(es)**

ADR / RID: Class: 9 Label: 9



IMDG: Class: 9 Label: 9



IATA: Class: 9 Label: 9

**14.4. Packing group**

ADR / RID, IMDG, IATA: III

**14.5. Environmental hazards**

ADR / RID: Environmentally Hazardous



IMDG: Marine Pollutant



IATA: Environmentally Hazardous

**14.6. Special precautions for user**

ADR / RID:	HIN - Kemler: 90	Limited Quantities: 5 L	Tunnel restriction code: (-)
	Special provision: 274, 335, 375, 601		
IMDG:	EMS: F-A, S-F	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 450 L	Packaging instructions: 964
	Passengers:	Maximum quantity: 450 L	Packaging instructions: 964
	Special provision:	A97, A158, A197, A215	

**14.7. Maritime transport in bulk according to IMO instruments**

Information not relevant

**SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substancePoint 75  
Point 28-29

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors  
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

**P10467 - FIBERFIP ADESIVO 800 COMP.A****SECTION 15. Regulatory information ... / >>**

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this health-dangerous chemical agent must undergo sanitary checks carried out in compliance with 2004/37/EC directive.

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Carc. 1B</b>	Carcinogenicity, category 1B
<b>Muta. 1B</b>	Germ cell mutagenicity, category 1B
<b>Repr. 1B</b>	Reproductive toxicity, category 1B
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H226</b>	Flammable liquid and vapour.
<b>H350</b>	May cause cancer.
<b>H340</b>	May cause genetic defects.
<b>H360F</b>	May damage fertility.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

## LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%

**P10467 - FIBERFIP ADESIVO 800 COMP.A****SECTION 16. Other information ... / >>**

- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise

**P10467 - FIBERFIP ADESIVO 800 COMP.A**

**SECTION 16. Other information ... / >>**

in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 07 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.