

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **P10468**
Product name **FIBERFIP ADESIVO 800 COMP.B**
Chemical name and synonym **A FIP 800 Component B**

UFI : **AP80-2083-D00G-GPKR**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Epoxy adhesive**

1.3. Details of the supplier of the safety data sheet

Name **Licata S.p.A.**
Full address **Via De Gasperi,155**
District and Country **92024 Canicatti (AG) Italia**

Tel. **+39 0922 856088**
Fax **+39 0922 831427**

e-mail address of the competent person responsible for the Safety Data Sheet **controllo-qualita@licataspa.it**

1.4. Emergency telephone number

For urgent inquiries refer to **NHS111in England: 111**
NHS24in Scotland: 111
NHS Direct in Wales: 111 or 0845 4647
In an emergency, if the patient has collapsed or is not breathing properly, call 999

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Reproductive toxicity, category 1B	H360FD	May damage fertility. May damage the unborn child.
Acute toxicity, category 4	H302	Harmful if swallowed.
Acute toxicity, category 4	H332	Harmful if inhaled.
Skin corrosion, category 1B	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity, category 1	H410	Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Licata S.p.A.		Revision nr.5 Dated 30/09/2024 Printed on 30/09/2024 Page n. 2 / 14 Replaced revision:4 (Dated 30/09/2024)	EN
P10468 - FIBERFIP ADESIVO 800 COMP.B			
SECTION 2. Hazards identification ... / >>			
Signal words:		Danger	
Hazard statements:		<div>H360FD H302+H332 H314 H317 H410 EUH071</div> <div>May damage fertility. May damage the unborn child. Harmful if swallowed or if inhaled. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Very toxic to aquatic life with long lasting effects. Corrosive to the respiratory tract. Restricted to professional users.</div>	
Precautionary statements:		<div>P260 P201 P305+P351+P338 P303+P361+P353 P280 P310</div> <div>Do not breathe dust / fume / gas / mist / vapours / spray. Obtain special instructions before use. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Wear protective gloves/ protective clothing / eye protection / face protection. Immediately call a POISON CENTER / doctor / . . .</div>	
Contains:		<div>Alchilfenolo 4,4-Isopropilidenedifenolo, reazione oligomerica con 1-cloro-2,3-epossipropano, prodotto di reazione con m-fenilenebis(metilammina) Triethylenetetramine M-PHENYLENEBIS (METHYLAMINE) 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE Fenolo, metilstirenato</div>	
2.3. Other hazards			
<div>On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.</div> <div>The product contains substances with endocrine disrupting properties in concentration ≥ 0,1%: Alchilfenolo</div>			
SECTION 3. Composition/information on ingredients			
3.2. Mixtures			
Contains:			
Identification		x = Conc. %	Classification (EC) 1272/2008 (CLP)
Fenolo, metilstirenato INDEX EC CAS68512-30-1		27 ≤ x < 28,5	Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 3 H412
3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE INDEX EC CAS220-666-8 CAS2855-13-2 REACH Reg.01-2119514687-32-XXXX		22,5 ≤ x < 24	Acute Tox. 4 H302, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1A H317 Skin Sens. 1A H317: ≥ 0,001% LD50 Oral: 1030 mg/kg
Triethylenetetramine INDEX EC CAS292-588-2 CAS90640-67-8 REACH Reg.01-2119487919-13-0000		16,5 ≤ x < 18	Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Chronic 3 H412 ATE Oral: 500 mg/kg, ATE Dermal: 1100 mg/kg
4,4-Isopropilidenedifenolo, reazione oligomerica con 1-cloro-2,3-epossipropano, prodotto di reazione con m-fenilenebis(metilammina) INDEX EC CAS500-302-7		12 ≤ x < 13,5	Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Chronic 3 H412 ATE Oral: 500 mg/kg, ATE Inhalation mists/powders: 1,5 mg/l, ATE Inhalation vapours: 11 mg/l
EPY 11.7.1 - SDS 1004.14			

P10468 - FIBERFIP ADESIVO 800 COMP.B**SECTION 3. Composition/information on ingredients** ... / >>

CAS 113930-69-1

BENZYL ALCOHOLINDEX 603-057-00-5 $7 \leq x < 8$

EC 202-859-9

CAS 100-51-6

REACH Reg. 01-2119492630-38-XXXX

AlchilfenoloINDEX $6 \leq x < 7$ **Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319****LD50 Oral: 1620 mg/kg, ATE Inhalation vapours: 11 mg/l****Repr. 1B H360FD, Skin Corr. 1C H314, Eye Dam. 1 H318, Aquatic Chronic 1 H410 M=10**

EC 310-154-3

CAS 121158-58-5

REACH Reg. 01-2119513207-49-XXXX

M-PHENYLENEBIS (METHYLAMINE)INDEX $6 \leq x < 7$ **Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1B H317, Aquatic Chronic 3 H412, EUH071****LD50 Oral: 930 mg/kg, LC50 Inhalation mists/powders: 1,34 mg/l/4h**

EC 216-032-5

CAS 1477-55-0

REACH Reg. 01-2119480150-50-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Rinse your mouth with running water. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER / doctor / . . .

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

<div>Licata S.p.A.</div> <div>P10468 - FIBERFIP ADESIVO 800 COMP.B</div>		<div>Revision nr.5</div> <div>Dated 30/09/2024</div> <div>Printed on 30/09/2024</div> <div>Page n. 4 / 14</div> <div>Replaced revision:4 (Dated 30/09/2024)</div>	EN
SECTION 5. Firefighting measures ... / >>			
5.2. Special hazards arising from the substance or mixture			
HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE			
Do not breathe combustion products.			
5.3. Advice for firefighters			
GENERAL INFORMATION			
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.			
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS			
Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).			
SECTION 6. Accidental release measures			
6.1. Personal precautions, protective equipment and emergency procedures			
Block the leakage if there is no hazard.			
Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.			
6.2. Environmental precautions			
The product must not penetrate into the sewer system or come into contact with surface water or ground water.			
6.3. Methods and material for containment and cleaning up			
Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.			
Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.			
6.4. Reference to other sections			
Any information on personal protection and disposal is given in sections 8 and 13.			
SECTION 7. Handling and storage			
7.1. Precautions for safe handling			
Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.			
7.2. Conditions for safe storage, including any incompatibilities			
Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.			
7.3. Specific end use(s)			
Information not available			
SECTION 8. Exposure controls/personal protection			
8.1. Control parameters			
Regulatory references:			
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58	
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021	
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)	
		EPY 11.7.1 - SDS 1004.14	

Licata S.p.A.						Revision nr.5 Dated 30/09/2024 Printed on 30/09/2024 Page n. 5 / 14 Replaced revision:4 (Dated 30/09/2024)				EN
P10468 - FIBERFIP ADESIVO 800 COMP.B										
SECTION 8. Exposure controls/personal protection ... / >>										
TLV-ACGIH			ACGIH 2023							
Alchilfenolo										
Predicted no-effect concentration - PNEC										
Normal value in fresh water						0,226		mg/kg dwt		
Normal value in marine water						0,0226		mg/kg dwt		
Health - Derived no-effect level - DNEL / DMEL										
Route of exposure	Effects on consumers				Effects on workers					
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic		
	local	systemic	local	systemic	local	systemic	local	systemic		
Inhalation							VND		1,7621 mg/m3	
Skin							VND		0,25 mg/kg bw/d	
M-PHENYLENEBIS (METHYLAMINE)										
Threshold Limit Value										
Type	Country	TWA/8h		STEL/15min		Remarks / Observations				
		mg/m3	ppm	mg/m3	ppm					
VLEP	FRA			0,1						
MV	SVN	0,1								
TLV-ACGIH				0,018 (C)		SKIN				
Predicted no-effect concentration - PNEC										
Normal value in fresh water						0,094		mg/l		
Normal value in marine water						0,0094		mg/l		
Normal value for fresh water sediment						12,4		mg/kg		
Normal value for marine water sediment						1,24		mg/kg		
Normal value of STP microorganisms						10		mg/l		
Normal value for the terrestrial compartment						244		mg/kg/d		
Health - Derived no-effect level - DNEL / DMEL										
Route of exposure	Effects on consumers				Effects on workers					
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic		
	local	systemic	local	systemic	local	systemic	local	systemic		
Inhalation							0,2 mg/m3		1,2 mg/m3	
Skin									0,33 mg/kg bw/d	
BENZYL ALCOHOL										
Threshold Limit Value										
Type	Country	TWA/8h		STEL/15min		Remarks / Observations				
		mg/m3	ppm	mg/m3	ppm					
AGW	DEU	22	5	44	10	SKIN	11			
MAK	DEU	22	5	44	10	SKIN				
MV	SVN	22	5	44	10	SKIN				
Predicted no-effect concentration - PNEC										
Normal value in fresh water						1		mg/l		
Normal value in marine water						0,1		mg/l		
Normal value for fresh water sediment						5,27		mg/kg/d		
Normal value for marine water sediment						0,527		mg/kg/d		
Normal value for water, intermittent release						2,31		mg/l		
Normal value for marine water, intermittent release						2,3		mg/l		
Normal value of STP microorganisms						39		mg/l		
Normal value for the terrestrial compartment						0,456		mg/kg		
Health - Derived no-effect level - DNEL / DMEL										
Route of exposure	Effects on consumers				Effects on workers					
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic		
	local	systemic	local	systemic	local	systemic	local	systemic		
Oral	VND	20 mg/kg/d	VND	4 mg/kg/d						
Inhalation					VND	110 mg/mq	VND	22 mg/mq		
Skin	VND	20 mg/kg/d	VND	4 mg/kg/d	VND	40 mg/kg/d	VND	8 mg/kg		
EPY 11.7.1 - SDS 1004.14										

<div>Licata S.p.A.</div> <div>P10468 - FIBERFIP ADESIVO 800 COMP.B</div>		<div>Revision nr.5 Dated 30/09/2024 Printed on 30/09/2024 Page n. 6 / 14 Replaced revision:4 (Dated 30/09/2024)</div> <div>EN</div>
SECTION 8. Exposure controls/personal protection ... / >>		
<div>Legend: (C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction. VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.</div> <div>Triethylenetetramine - Trietilentetrammina (CAS: 90640-67-8):</div> <div>PNEC: acqua dolce: 0,135 mg/l acqua di mare: 0,0027mg/l emissione saltuaria: 0,2 mg/l Sedimento (acqua dolce): 2,08 mg/kg Sedimento (acqua di mare): 0,123 mg/kg Suolo: 1,67 mg/kg STP: 8 mg/l.</div> <div>8.2. Exposure controls</div> <div>As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. When choosing personal protective equipment, ask your chemical substance supplier for advice. Personal protective equipment must be CE marked, showing that it complies with applicable standards. Provide an emergency shower with face and eye wash station.</div> <div>HAND PROTECTION Protect hands with category III work gloves. The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.</div> <div>SKIN PROTECTION Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.</div> <div>EYE PROTECTION Wear airtight protective goggles (see standard EN ISO 16321). In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.</div> <div>RESPIRATORY PROTECTION Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.</div> <div>ENVIRONMENTAL EXPOSURE CONTROLS The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards. Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.</div>		
SECTION 9. Physical and chemical properties		
9.1. Information on basic physical and chemical properties		
<div>Properties</div> <div>Appearance</div> <div>Colour</div> <div>Odour</div> <div>Melting point / freezing point</div> <div>Initial boiling point</div> <div>Flammability</div> <div>Lower explosive limit</div> <div>Upper explosive limit</div> <div>Flash point</div> <div>Auto-ignition temperature</div> <div>Decomposition temperature</div> <div>pH</div> <div>Kinematic viscosity</div>	<div>Value</div> <div>not available</div> <div>not available</div> <div>not available</div> <div>not available</div> <div>> 200 °C</div> <div>not available</div> <div>not available</div> <div>not available</div> <div>> 100 °C</div> <div>not available</div> <div>not available</div> <div>basico</div> <div>not available</div>	<div>Information</div>
<div>EPY 11.7.1 - SDS 1004.14</div>		

P10468 - FIBERFIP ADESIVO 800 COMP.B**SECTION 9. Physical and chemical properties** ... / >>

Solubility	not available
Partition coefficient: n-octanol/water	not available
Vapour pressure	not available
Density and/or relative density	1
Relative vapour density	not available
Particle characteristics	not applicable

9.2. Other information**9.2.1. Information with regard to physical hazard classes**

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU)	7,77 % - 77,73	g/litre
VOC (volatile carbon)	6,04 % - 60,37	g/litre

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F.Possibility of explosion.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

BENZYL ALCOHOL

May react dangerously with: hydrobromic acid,iron,oxidising agents,sulphuric acid.Risk of explosion on contact with: phosphorus trichloride.

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

May react dangerously with: strong oxidising agents,concentrated inorganic acids.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

BENZYL ALCOHOL

Avoid exposure to: air,sources of heat,naked flames.

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Avoid contact with: strong acids,strong oxidants.

10.5. Incompatible materials**Triethylenetetramine**

- Trietilentetramina (CAS: 90640-67-8):

Mescolando il prodotto con acqua genera calore. Si possono verificare spruzzi e il prodotto può bollire.

Evitare il contatto con materiali ossidanti.

Evitare il contatto con: Acidi, acrilati, alcool, aldeidi, idrocarburi alogenati, chetoni, nitriti, metalli come: ottone, bronzo, rame, leghe di rame,

materiali assorbenti come: pannocchie, assorbenti organici umidi, torbiera, segatura.

BENZYL ALCOHOL

Incompatible with: sulphuric acid,oxidising substances,aluminium.

10.6. Hazardous decomposition products

Information not available

P10468 - FIBERFIP ADESIVO 800 COMP.B**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	Acute Tox. 4
ATE (Inhalation - vapours) of the mixture:	Acute Tox. 4
ATE (Inhalation - gas) of the mixture:	Acute Tox. 4
ATE (Oral) of the mixture:	1012,49 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

Corrosive to the respiratory tract.

4,4-Isopropilidenedifenolo, reazione oligomerica con 1-cloro-2,3-eossipropano, prodotto di reazione con m-fenilenebis(metilammina)

ATE (Oral):	500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
ATE (Inhalation mists/powders):	1,5 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
ATE (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

Alchilfenolo	
LD50 (Dermal):	> 2000 mg/kg Rabbit
LD50 (Oral):	2140 mg/kg Rat

Triethylenetetramine	
LD50 (Dermal):	550 mg/kg Rabbit
ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	2,78 mg/kg Rat
ATE (Oral):	500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

M-PHENYLENEBIS (METHYLAMINE)	
LD50 (Dermal):	> 3100 mg/kg Rat
LD50 (Oral):	930 mg/kg Rat - Sprague-Dawley
LC50 (Inhalation mists/powders):	1,34 mg/l/4h

BENZYL ALCOHOL	
LD50 (Dermal):	2000 mg/kg Rabbit
LD50 (Oral):	1620 mg/kg Rat
LC50 (Inhalation vapours):	> 4,178 mg/l/4h Rat
ATE (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

P10468 - FIBERFIP ADESIVO 800 COMP.B**SECTION 11. Toxicological information** ... / >>**3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE**

LD50 (Dermal):	> 2000 mg/kg Coniglio
LD50 (Oral):	1030 mg/kg Ratto
LC50 (Inhalation mists/powders):	> 5 mg/l/4h Ratto

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

May damage fertility - May damage the unborn child

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product contains the following endocrine disruptors in concentrations of 0.1% or greater by weight that may have endocrine disrupting effects on humans and cause adverse effects on the exposed individual or his or her progeny:

Alchilfenolo

SECTION 12. Ecological information

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity**M-PHENYLENEBIS (METHYLAMINE)**

LC50 - for Fish	100 mg/l/96h Oryzias latipes
EC50 - for Crustacea	100 mg/l/48h Daphnia magna

BENZYL ALCOHOL

LC50 - for Fish	> 100 mg/l/96h
EC50 - for Crustacea	> 100 mg/l/48h Daphnia magna

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	1,5 mg/l Alga verde

12.2. Persistence and degradability

<div>Licata S.p.A.</div> <div>P10468 - FIBERFIP ADESIVO 800 COMP.B</div>		Revision nr.5 Dated 30/09/2024 Printed on 30/09/2024 Page n. 10 / 14 Replaced revision:4 (Dated 30/09/2024)	EN
SECTION 12. Ecological information ... / >>			
M-PHENYLENEBIS (METHYLAMINE) Degradability: information not available			
BENZYL ALCOHOL Degradability: information not available			
3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE NOT rapidly degradable			
12.3. Bioaccumulative potential			
Information not available			
12.4. Mobility in soil			
Information not available			
12.5. Results of PBT and vPvB assessment			
On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.			
12.6. Endocrine disrupting properties			
Based on the available data, the product contains the following endocrine disruptors in concentrations of 0.1% or greater by weight that may have endocrine disrupting effects on the environment and on animal species causing adverse effects on the exposed organisms or on their progeny: Alchilfenolo			
12.7. Other adverse effects			
Information not available			
SECTION 13. Disposal considerations			
13.1. Waste treatment methods			
Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.			
SECTION 14. Transport information			
14.1. UN number or ID number			
ADR / RID, IMDG, IATA: UN 2735			
14.2. UN proper shipping name			
ADR / RID: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Triethylenetetramine; 3-aminomethyl-3,5,5-trimethylcyclohexylamine)			
IMDG: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Triethylenetetramine; 3-aminomethyl-3,5,5-trimethylcyclohexylamine)			
IATA: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Triethylenetetramine; 3-aminomethyl-3,5,5-trimethylcyclohexylamine)			
EPY 11.7.1 - SDS 1004.14			

P10468 - FIBERFIP ADESIVO 800 COMP.B**SECTION 14. Transport information** ... / >>**14.3. Transport hazard class(es)**

ADR / RID: Class: 8 Label: 8



IMDG: Class: 8 Label: 8



IATA: Class: 8 Label: 8

**14.4. Packing group**

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous



IMDG: Marine Pollutant



IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 80 Special provision: 274	Limited Quantities: 5 L	Tunnel restriction code: (E)
IMDG:	EMS: F-A, S-B	Limited Quantities: 5 L	
IATA:	Cargo: Passengers: Special provision:	Maximum quantity: 60 L Maximum quantity: 5 L A3, A803	Packaging instructions: 856 Packaging instructions: 852

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: E1

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product	
Point	3
Contained substance	
Point	75
Point	30

Alchilfenolo
REACH Reg.: 01-2119513207-49-XXXX

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

Alchilfenolo
REACH Reg.: 01-2119513207-49-XXXX

Substances subject to authorisation (Annex XIV REACH)

None

P10468 - FIBERFIP ADESIVO 800 COMP.B

SECTION 15. Regulatory information ... / >>

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Repr. 1B	Reproductive toxicity, category 1B
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
Skin Sens. 1B	Skin sensitization, category 1B
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H360FD	May damage fertility. May damage the unborn child.
H302+H332	Harmful if swallowed or if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level

P10468 - FIBERFIP ADESIVO 800 COMP.B**SECTION 16. Other information ... / >>**

- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
 23. Delegated Regulation (UE) 2023/707
 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
 24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

SECTION 16. Other information ... / >>

01 / 02 / 03 / 08 / 09 / 10 / 11 / 12 / 15 / 16.