

P10489 - ResinFIP_Epobond_T160_COMP.B**Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Code: **P10489**
 Product name: **ResinFIP_Epobond_T160_COMP.B**
 UFI: **V6N0-V0R9-E00T-3EPD**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **two -component epoxy resin**

1.3. Details of the supplier of the safety data sheet

Name: **Licata S.p.A.**
 Full address: **Via De Gasperi,155**
 District and Country: **92024 Canicatti (AG) Italia**
 Tel.: **+39 0922 856088**
 Fax: **+39 0922 831427**
 e-mail address of the competent person responsible for the Safety Data Sheet: **controllo-qualita@licataspa.it**

1.4. Emergency telephone number

For urgent inquiries refer to:
NHS111 in England: 111
NHS24 in Scotland: 111
NHS Direct in Wales: 111 or 0845 4647
In an emergency, if the patient has collapsed or is not breathing properly, call 999

SECTION 2. Hazards identification**2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Reproductive toxicity, category 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Skin corrosion, category 1B	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity, category 2	H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



P10489 - ResinFIP_Epobond_T160_COMP.B**SECTION 2. Hazards identification** ... / >>

Signal words: Danger

Hazard statements:

H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H314 Causes severe skin burns and eye damage.
H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
EUH071 Corrosive to the respiratory tract.

Precautionary statements:

P260 Do not breathe dust / fume / gas / mist / vapours / spray.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P310 Immediately call a POISON CENTER / doctor / . . .
P264 Wash . . . thoroughly after handling.

Contains:

Alchilfenolo
 N-Aminoethylpiperazine
 M-PHENYLENEBIS (METHYLAMINE)
 Polymeric reaction
 products of
 formaldehyde and 4-
 nonylpenol and
 triethylenetetramine
 and 2-piperazin-1-
 ylethylamine
 FELDSPATO

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product contains substances with endocrine disrupting properties in concentration \geq 0,1%:
 Alchilfenolo

SECTION 3. Composition/information on ingredients**3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
FELDSPATO		
INDEX	$30 \leq x < 32,5$	Eye Irrit. 2 H319, STOT SE 3 H335
EC	270-666-7	
CAS	68476-25-5	
M-PHENYLENEBIS (METHYLAMINE)		
INDEX	$13,5 \leq x < 15$	Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1B H317, Aquatic Chronic 3 H412, EUH071 LD50 Oral: 930 mg/kg, ATE Inhalation vapours: 11 mg/l
EC	216-032-5	
CAS	1477-55-0	
REACH Reg.	01-2119480150-50-XXXX	
Polymeric reaction		
products of		
formaldehyde and 4-		
nonylpenol and		

P10489 - ResinFIP_Epobond_T160_COMP.B**SECTION 3. Composition/information on ingredients ... / >>****triethylenetetramine
and 2-piperazin-1-
ylethylamine**

<i>INDEX</i>		$7 \leq x < 8$	Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317
--------------	--	----------------	---

<i>EC</i>	922-006-0		
-----------	-----------	--	--

<i>CAS</i>			
------------	--	--	--

QUARTZ

<i>INDEX</i>		$6 \leq x < 7$	Substance with a community workplace exposure limit.
--------------	--	----------------	---

<i>EC</i>	238-878-4		
-----------	-----------	--	--

<i>CAS</i>	14808-60-7		
------------	------------	--	--

BENZYL ALCOHOL

<i>INDEX</i>	603-057-00-5	$5 \leq x < 6$	Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319
--------------	--------------	----------------	--

<i>EC</i>	202-859-9		LD50 Oral: 1620 mg/kg, ATE Inhalation vapours: 11 mg/l
-----------	-----------	--	---

<i>CAS</i>	100-51-6		
------------	----------	--	--

<i>REACH Reg.</i>	01-2119492630-38-XXXX		
-------------------	-----------------------	--	--

N-Aminoethylpiperazine

<i>INDEX</i>	612-105-00-4	$4,5 \leq x < 5$	Repr. 2 H361, Acute Tox. 3 H311, Acute Tox. 4 H302, STOT RE 1 H372, Skin
--------------	--------------	------------------	---

<i>EC</i>	205-411-0		Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Chronic 3 H412
-----------	-----------	--	--

<i>CAS</i>	140-31-8		ATE Oral: 500 mg/kg, LD50 Dermal: 866 mg/kg
------------	----------	--	--

<i>REACH Reg.</i>	01-2119471486-30-XXXX		
-------------------	-----------------------	--	--

Alchilfenolo

<i>INDEX</i>		$3 \leq x < 3,5$	Repr. 2 H361, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Aquatic Chronic 1 H410
--------------	--	------------------	--

<i>EC</i>			M=1
-----------	--	--	------------

<i>CAS</i>	310-154-3		
------------	-----------	--	--

<i>CAS</i>	121158-58-5		
------------	-------------	--	--

<i>REACH Reg.</i>	01-2119513207-49-XXXX		
-------------------	-----------------------	--	--

QUARTZ

<i>INDEX</i>		$0 < x < 0,05$	STOT RE 1 H372
--------------	--	----------------	-----------------------

<i>EC</i>	238-878-4		
-----------	-----------	--	--

<i>CAS</i>	14808-60-7		
------------	------------	--	--

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Rinse your mouth with running water. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER / doctor / . . .

SECTION 4. First aid measures ... / >>

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory references:

DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

Alchilfenolo**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,226	mg/kg dwt
Normal value in marine water	0,0226	mg/kg dwt

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation							VND	1,7621 mg/m3
Skin							VND	0,25 mg/kg bw/d

N-Aminoethylpiperazine**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,058	mg/l
Normal value in marine water	0,0058	mg/l
Normal value for fresh water sediment	215	mg/kg
Normal value for marine water sediment	21,5	mg/kg
Normal value for marine water, intermittent release	0,58	mg/l
Normal value for the terrestrial compartment	42,9	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	VND	5,3 mg/m3	VND	0,9 mg/m3	VND	3,6 mg/m3	VND	21,4 mg/m3

P10489 - ResinFIP_Epobond_T160_COMP.B

SECTION 8. Exposure controls/personal protection ... / >>

M-PHENYLENEBIS (METHYLAMINE)

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
VLEP	FRA			0,1		
MV	SVN	0,1				
TLV-ACGIH				0,018 (C)		SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,094	mg/l
Normal value in marine water	0,0094	mg/l
Normal value for fresh water sediment	12,4	mg/kg
Normal value for marine water sediment	1,24	mg/kg
Normal value for water, intermittent release	0,152	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	2,44	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation							0,2 mg/m3	1,2 mg/m3
Skin								0,33 mg/kg bw/d

QUARTZ

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
VLA	ESP		0,05			RESP
VLEP	FRA	0,1				RESP
GVI/KGVI	HRV	0,1				
VLEP	ITA	0,1				RESP
MV	SVN	0,15				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				RESP

QUARTZ

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
VLA	ESP		0,05			RESP
VLEP	FRA	0,1				RESP
GVI/KGVI	HRV	0,1				
VLEP	ITA	0,1				RESP
MV	SVN	0,15				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				RESP

P10489 - ResinFIP_Epobond_T160_COMP.B**SECTION 8. Exposure controls/personal protection ... / >>****BENZYL ALCOHOL****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	22	5	44	10	SKIN 11
MAK	DEU	22	5	44	10	SKIN
MV	SVN	22	5	44	10	SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	1	mg/l
Normal value in marine water	0,1	mg/l
Normal value for fresh water sediment	5,27	mg/kg/d
Normal value for marine water sediment	0,527	mg/kg/d
Normal value for water, intermittent release	2,31	mg/l
Normal value for marine water, intermittent release	2,3	mg/l
Normal value of STP microorganisms	39	mg/l
Normal value for the terrestrial compartment	0,456	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	VND	20 mg/kg/d	VND	4 mg/kg/d				
Inhalation					VND	110 mg/mq	VND	22 mg/mq
Skin	VND	20 mg/kg/d	VND	4 mg/kg/d	VND	40 mg/kg/d	VND	8 mg/kg

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

P10489 - ResinFIP_Epobond_T160_COMP.B**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	not available	
Colour	not available	
Odour	not available	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	12	
Kinematic viscosity	not available	
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	not available	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU) 20,55 %

VOC (volatile carbon) 4,47 %

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

N-Aminoethylpiperazine

Stable in normal conditions of use and storage.

BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F.Possibility of explosion.

CALCIUM CARBONATE

Decomposes at temperatures above 800°C/1472°F.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

N-Aminoethylpiperazine

Stable in normal conditions of use and storage.

QUARTZ

Stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

BENZYL ALCOHOL

May react dangerously with: hydrobromic acid,iron,oxidising agents,sulphuric acid.Risk of explosion on contact with: phosphorus trichloride.

P10489 - ResinFIP_Epobond_T160_COMP.B**SECTION 10. Stability and reactivity** ... / >>**10.4. Conditions to avoid**

None in particular. However the usual precautions used for chemical products should be respected.

QUARTZ

Decomposes if exposed to: sources of heat.

BENZYL ALCOHOL

Avoid exposure to: air, sources of heat, naked flames.

10.5. Incompatible materials**N-Aminoethylpiperazine**

Incompatible with: oxidising agents, metals, Nitrous acid, nitric acid, Other nitrogen-forming agents, Combustible material.

QUARTZ

Incompatible with: Oxidants.

BENZYL ALCOHOL

Incompatible with: sulphuric acid, oxidising substances, aluminium.

CALCIUM CARBONATE

Incompatible with: acids.

10.6. Hazardous decomposition products**CALCIUM CARBONATE**

May develop: calcium oxides, carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**N-Aminoethylpiperazine**

- 2-piperazin-1-ylethylamine (CAS 140-31-8):

Test: LD50 - Via: Skin - Species: Rabbit = 866-1260 mg / kg

Test: LD50 - Via: Oral - Species: Rat = 1470 to 2140 mg / kg

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: > 20 mg/l

ATE (Oral) of the mixture: >2000 mg/kg

ATE (Dermal) of the mixture: >2000 mg/kg

Corrosive to the respiratory tract.

Alchilfenolo

LD50 (Dermal): > 2000 mg/kg Rabbit

LD50 (Oral): 2140 mg/kg Rat

N-Aminoethylpiperazine

LD50 (Dermal): 866 mg/kg Rabbit

LD50 (Oral): 2097 mg/kg RABBIT

ATE (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP

P10489 - ResinFIP_Epobond_T160_COMP.B**SECTION 11. Toxicological information ... / >>**

(figure used for calculation of the acute toxicity estimate of the mixture)

M-PHENYLENEBIS (METHYLAMINE)

LD50 (Dermal): > 3100 mg/kg Rat
 LD50 (Oral): 930 mg/kg Rat - Sprague-Dawley
 LC50 (Inhalation vapours): 1,34 mg/l/4h Ratto
 ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
 (figure used for calculation of the acute toxicity estimate of the mixture)

AMORPHOUS SILICATE HYDRATE

LD50 (Dermal): > 2000 mg/kg Ratto
 LD50 (Oral): > 5000 mg/kg Ratto
 LC50 (Inhalation mists/powders): > 2,2 mg/l/1h Ratto

BENZYL ALCOHOL

LD50 (Dermal): 2000 mg/kg Rabbit
 LD50 (Oral): 1620 mg/kg Rat
 LC50 (Inhalation vapours): > 4,178 mg/l/4h Rat
 ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
 (figure used for calculation of the acute toxicity estimate of the mixture)

CALCIUM CARBONATE

LD50 (Oral): 6450 mg/kg Rat

SKIN CORROSION / IRRITATION

Corrosive for the skin
 Classification according to the experimental Ph value

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Suspected of damaging fertility or the unborn child

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product contains the following endocrine disruptors in concentrations of 0.1% or greater by weight that may have endocrine disrupting effects on humans and cause adverse effects on the exposed individual or his or her progeny:
 Alchilfenolo

P10489 - ResinFIP_Epobond_T160_COMP.B**SECTION 12. Ecological information**

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

N-Aminoethylpiperazine

- 2-piperazin-1-ylethylamine (CAS 140-31-8):

Test: LC50 - Species: Fish - h Duration: 96 - mg / l: 1800

Te t: EC50 - Species: Daphnia - h Duration: 48 - mg / l: 58

Test: LC50 - Species: Algae - h Duration: 72 - mg / l: 494

Test: EC50 - Species: Algae - mg / l: 1000

N-Aminoethylpiperazine

LC50 - for Fish

> 100 mg/l/96h

EC50 - for Crustacea

58 mg/l/48h Daphnia

EC50 - for Algae / Aquatic Plants

> 100 mg/l/72h Alga verde

M-PHENYLENEBIS (METHYLAMINE)

LC50 - for Fish

87,6 mg/l/96h Oryzias latipes

EC50 - for Crustacea

15,2 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants

26,8 mg/l/72h

Chronic NOEC for Crustacea

4,7 mg/l

Chronic NOEC for Algae / Aquatic Plants

16,7 mg/l

AMORPHOUS SILICATE HYDRATE

LC50 - for Fish

> 10000 mg/l/96h

BENZYL ALCOHOL

LC50 - for Fish

> 100 mg/l/96h

EC50 - for Crustacea

> 100 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants

770 mg/l/72h

Chronic NOEC for Crustacea

51 mg/l Daphnia magna

12.2. Persistence and degradability

Alchilfenolo

Degradability: information not available

N-Aminoethylpiperazine

Degradability: information not available

M-PHENYLENEBIS (METHYLAMINE)

Solubility in water

100 mg/l

NOT rapidly degradable

AMORPHOUS SILICATE HYDRATE

Degradability: information not available

Sostanza inorganica

QUARTZ

Degradability: information not available

QUARTZ

Degradability: information not available

BENZYL ALCOHOL

Rapidly degradable

CALCIUM CARBONATE

Solubility in water

0,1 - 100 mg/l

12.3. Bioaccumulative potential

P10489 - ResinFIP_Epobond_T160_COMP.B**SECTION 12. Ecological information** ... / >>

M-PHENYLENEBIS (METHYLAMINE)

Partition coefficient: n-octanol/water

0,18 Log Kow

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessmentOn the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.**12.6. Endocrine disrupting properties**

Based on the available data, the product contains the following endocrine disruptors in concentrations of 0.1% or greater by weight that may have endocrine disrupting effects on the environment and on animal species causing adverse effects on the exposed organisms or on their progeny:

Alchilfenolo

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number or ID number**

ADR / RID, IMDG, IATA: UN 3267

14.2. UN proper shipping name

ADR / RID: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (M-PHENYLENEBIS (METHYLAMINE) ; Polymeric reaction products of formaldehyde and 4-nonylphenol and triethylenetetramine and 2-piperazin-1-ylethylamine)

IMDG: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (M-PHENYLENEBIS (METHYLAMINE) ; Polymeric reaction products of formaldehyde and 4-nonylphenol and triethylenetetramine and 2-piperazin-1-ylethylamine; Alchilfenolo)

IATA: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (M-PHENYLENEBIS (METHYLAMINE) ; Polymeric reaction products of formaldehyde and 4-nonylphenol and triethylenetetramine and 2-piperazin-1-ylethylamine)

P10489 - ResinFIP_Epobond_T160_COMP.B**SECTION 14. Transport information** ... / >>**14.3. Transport hazard class(es)**

ADR / RID: Class: 8 Label: 8



IMDG: Class: 8 Label: 8



IATA: Class: 8 Label: 8

**14.4. Packing group**

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous



IMDG: Marine Pollutant



IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 80 Special provision: 274	Limited Quantities: 1 lt	Tunnel restriction code: (E)
IMDG:	EMS: F-A, S-B	Limited Quantities: 1 lt	
IATA:	Cargo: Passengers: Special provision:	Maximum quantity: 30 L Maximum quantity: 1 L A3, A803	Packaging instructions: 855 Packaging instructions: 851

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>	
Point	3
<u>Contained substance</u>	
Point	75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

Alchilfenolo
REACH Reg.: 01-2119513207-49-XXXX

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

P10489 - ResinFIP_Epobond_T160_COMP.B**SECTION 15. Regulatory information ... / >>**

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Repr. 2	Reproductive toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1B	Skin sensitization, category 1B
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H361	Suspected of damaging fertility or the unborn child.
H311	Toxic in contact with skin.
H302	Harmful if swallowed.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%

P10489 - ResinFIP_Epobond_T160_COMP.B**SECTION 16. Other information ... / >>**

- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

P10489 - ResinFIP_Epobond_T160_COMP.B**SECTION 16. Other information ... / >>**

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:
The following sections were modified:
01.